

EverSecure™

16 Channel Stand-Alone DVR System with Removable HDD **DVR-2216M**

Features



Front View



Rear View

- Supports 2 removable HDD (up to 250 GB each) recording, IDE type
- Wavelet Compression Format
- Built-in 16 channel color multiplexing function
- Supports 4, 7, 9, 10, 13, 16 channels video inputs.
- Supports RS-232 or RS-485 remote control
- Up to 72 images/sec video display, 25 images/sec video recording (NTSC)
- 4 level video quality adjustable
- Motion trigger recording function
- 16 alarm inputs, 1 alarm output
- Video loss detected on each channel capable for recording up to 160 events
- Various recording modes: manual, alarm, timer, motion
- Power loss memory function
- Quick multiple search by date/time/alarm list
- Independent title setting (up to 6 characters) for each channel

Technical Specifications:

- | | |
|------------------------------------|---|
| • Remote Communication Protocol: | RS-232 or RS-485 |
| • Video Format : | NTSC/EIA or PAL/CCIR |
| • Hard Disk Storage: | IDE type, UDMA 66, supported up to 250 GB HDD |
| • Recording Mode: | Manual, Alarm, Timer, Motion Trigger |
| • Refresh Rate: | Up to 72 images/sec (NTSC), 60 images/sec (PAL) |
| • Recording Rate: | Up to 25 images/sec (NTSC), 18 images/sec (PAL) |
| • Camera Input Signal & Loop back: | Composite video signal 1.0 Vp-p 75 Ω BNC, 9 channel |
| • Main & Call Monitor Output: | Composite video signal 1.0 Vp-p 75 Ω BNC |
| • Display: | Full Screen, Quad Screen, Picture in Picture, Zoom in/out |
| • Motion Detect Area: | 15 x 12 targets per camera (NTSC), 15 x 14 targets per camera (PAL) |
| • Motion Detection Sensitivity: | 256 Levels |
| • Video Loss Detection: | Yes |
| • Dwell Time: | Programmable (1~10 sec) |
| • Picture in Picture: | Yes |
| • Picture Zoom: | 2 x 2 (Movable) |
| • Video Adjustability: | Color/Contrast/Brightness adjustable |
| • Audio Input/Output: | 4 Audio Inputs (RCA), 2 Audio Outputs (RCA) |
| • Alarm Input/Output: | Input: TTL Alarm Input, High (5V), Low (GND); Output: COM/N.O. |
| • Operation Temperature: | 10 - 40°C (47-104°F) |
| • Power Supply: | AC 100-240V +/- 10% Switching adaptor |
| • Dimension: | 17" (W) x 12.75" (H) x 4.4" (D) |
| • Weight: | 12.5Lb |