

DX-VP4, DX-VP4C, DX-VP4C-HR
Vandal Proof B/W & Color 4" Dome Camera



Vandal Proof Dome Cameras are designed to provide a secure housing for your cameras. They are the best choice for those locations where individuals can damage the viewing system. Constructed with a Poly-Carbonate Armor dome & ultra hard grade aluminum die-cast base. It provides a very secure environment for your most critical surveillance applications. Available with either B/W or Color Cameras.

Features:

- SONY 1/3" CCD Sensor
- 400(B/W) / 380(Color) / 470(Color,Hi-Res) TV Lines
- 0.1(B/W) / 0.5(Color) Lux
- AES, AGC, AWB & BLC for Hi-Res Camera
- Powered by 12 VDC Regulated

Specifications	B/W	Color	Color
Model No.	DX-VP4	DX-VP4C	DX-VP4C-HR
Image Pick-up Device	SONY 1/3" B/W CCD Sensor	SONY 1/3" Color Sensor	SONY 1/4" Color Super HAD CCD Sensor
Horizontal Resolution	400 TV Lines	380 TV Lines	470 TV Lines
Minimum Illumination	0.1 Lux @F2.0	0.5 LUX @F2.0	0.4 LUX @F2.0
S/N Ratio	More than 48dB	More than 48dB	More than 48dB
Gamma Characteristics	0.45	0.45	0.45
Lens Furnished	3.6 mm board lens	3.6 mm board lens	3.6 mm board lens
Auto Gain Control	Yes	Yes	High/Low Switch-able
Synchronous System	Internal, Negative Sync.	Internal, Negative Sync.	Internal, Negative Sync.
Video Output	1 Vp-p /75 Ohms	1 Vp-p /75 Ohms	1 Vp-p /75 Ohms
Audio Output	None	None	None
Power Supply	12VDC +/- 10% / 110mA	12VDC +/- 10% / 110mA	12VDC /24 VAC
Operating Temperature	-10 ~ 50°C (14 ~ 122°F)	-10 ~ 50°C (14 ~ 122°F)	-10 ~ 50°C (14 ~ 122°F)