

Audio/Video Modulator CVS-500



Features

- Add Security Camera to TV Channel
- Use standard TV set as CCTV monitor
- Output channel tunable to UHF 14-69 and CATV 65-135(excluding CH 95-99)
- Last Channel Memory
- Easy push button channel up/down operation
- Microprocessor controlled tuning
- Digital crystal PLL modulation
- Built-in splitter/combiner
- Stereo audio input
- LED channel display

Specifications

RF:

Output Frequency Range:	470-863 MHz
Output Channels	UHF: CH14-69(NTSC)
	ULTRA: CH91-135(NTSC)
	CABLE: CH65-125
	(excluding CH95-99)
Output Level:	28 dBmV TYP
Output Impedance:	75 Ohm
Frequency Accuracy/Stability:	+/-5KHz@0-50°C
Aural/Visual Carrier Ratio:	-17 dB +/- 2dB

VIDEO

Input Level:	1 Vp-p
Input Impedance	75 Ohm
S/N Ratio:	52 dB. TYP
Frequency Response:	+/- 1 dB
Modulation Depth:	75% +/-10%
Differential Gain:	less than 8%
Differential Phase	less than 8%

Ordering Information

- **UPS, FedEx Delivery**
- **Visa, Master, Discover cards accepted**
- **Call (847) 303-9700 for Distributor Program**